

RECEIVED

ORIGINAL

MAY 3 0 2008

Department of Environmental Quality
State Air Program

PRE-PERMIT CONSTRUCTION APPROVAL
AND PERMIT TO CONSTRUCT APPLICATION for
DF-AP #3, LLC,
DOUBLE A DAIRY
JEROME, IDAHO

May 29, 2008

Kleinfelder Project Number: 93142

All Rights Reserved Copyright 2008

This document was prepared for use only by the client, only for the purposes stated, and within a reasonable time from issuance. Non-commercial, educational and scientific use of this report by regulatory agencies is regarded as a "fair use" and not a violation of copyright. Regulatory agencies may make additional copies of this document for internal use. Copies may also be made available to the public as required by law. The reprint must acknowledge the copyright and indicate that permission to reprint has been received.



Prepared for:

DF-AP #3, LLC Salashan Parkway P.O. Box 2708 Ferndale, Washington 98248

PRE-PERMIT CONSTRUCTION APPROVAL AND PERMIT TO CONSTRUCT APPLICATION for DF-AP #3, LLC, DOUBLE A DAIRY 305 County Line Road Jerome, Idaho 83338

Kleinfelder Job No: 93142

Prepared by:

Kelli Wetzel

Air Quality Engineer

Reviewed by:

Estee Lafrenz, P.E. Air Quality Engineer

May 29, 2008

KLEINFELDER WEST, INC.

2315 S. Cobalt Point Way Meridian Idaho 83642 (208) 893-9700



TABLE OF CONTENTS

SEC	TION		<u>PAGE</u>
1	1.1. Pro	S DESCRIPTION	1
2	PRE PER	RMIT CONSTRUCTION ELIGIBILITY	2
3	3.1. Ma	ABLE REQUIREMENTS	3 3
4	4.1. Eq 4.2. So 4.3. En 4.4. Po	IAL EMISSION ESTIMATES uipment and Source Description urce Parameters nission Factors tential to Emit / Emissions Estimates nission Limits	7 8 8 9
5	AMBIEN	T IMPACT ASSESSMENTS	12
TAB	Table 3-1: Table 4-1: Table 4-2: Table 5-1: Table 5-2: Table 5-3: Table 5-4:	Summary of 40 CFR 60, Subpart JJJJ Equipment Description Potential Emission Rates for Genset Generators Modeling Results for Criteria Pollutants Modeling Results for TAPs Modeling Results for Criteria Pollutants Modeling Results for TAPs	
FIG	URES Figure 1: Figure 2: Figure 3: Figure 4:	Site Location Map Vicinity Map Facility Detail Process Flow Diagram	



APPENDICES

Appendix A: Permit to Construct Application Forms

Form CS: Cover Sheet

Form GI: Facility Information

Form EU1: Industrial Engine Information (Engine 1)
Form EU1: Industrial Engine Information (Engine 2)

Form EU1: Industrial Engine Information (Engine 3)
Form EU1: Industrial Engine Information (Engine 4)

Form EU1: Industrial Engine Information (Engine 5)

Form EU1: Industrial Engine Information (Engine 6)

Forms EI-CP1 – EI-CP4: Emissions Inventory – Criteria Pollutants Form PP: Plot Plan

Form PP: Plot Plan
Forms MI1 – MI4: Modeling

Form FRA: Federal Regulation Applicability

Appendix B: Modeling Protocol

Appendix C: Modeling Protocol Approval Letter

Appendix D: Emission Calculations and Screen3 Outputs

Appendix E: Affidavit of Publication – Public Notice Meeting

Appendix F: EPA letter regarding 40 CFR 60, Subpart JJJJ



1 PROCESS DESCRIPTION

DF-AP #3, LLC proposes to construct an anaerobic digester renewable energy system on property leased from Double A Dairy. The site is located in Jerome, Idaho and presented in Figures 1 through 3. The facility is within Lincoln County, Idaho which is designated attainment or unclassifiable for criteria pollutants.

1.1. Process Description

Manure from the dairy will be pumped into the anaerobic digester where the naturally occurring digestion process will result in the production of methane gas. Methane gas will be collected in the anaerobic digester and used as fuel in six Genset reciprocating internal combustion engines. The generators will produce electricity that will be sold to the local utility. Heat produced from the Genset electrical generators will be used to maintain the operating temperature in the digester and as process heat for the dairy. The post digester manure is separated so the liquid portion can be utilized for irrigation and fertilizer while the solids are utilized as bedding and a soil amendment. A process flow diagram is presented in Figure 4.

The project includes the installation of the manure digester and generators. Double A Dairy will operate the dairy and manage the solids and wastewater generated by the process. This permit application is being submitted to allow construction and operation of the digester and electrical generating system. Air emissions from the system are released through the six stacks associated with the Genset generators and an emergency flare that would be used in the event the generators are taken offline. Characteristics of the emissions from all of the emission points are the same.

The proposed anaerobic digester renewable energy system will be constructed by Andgar Corporation and operated by DF-AP #3, LLC on property leased from the Double A Dairy. The generator emissions will result in criteria pollutant emissions of carbon monoxide, particulate matter, nitrogen oxides, sulfur dioxide and volatile organic compounds. The generators will also emit toxic air pollutants (TAPs).

1.2. Facility Classifications

SIC: 4911

The facility is classified by the Standard Industrial Classification # 4911 for Electric Services.

NAICS: 237130

The facility is classified by the North American Industry Classification System # 237130 for Alternative Energy Structure Construction.



2 PRE PERMIT CONSTRUCTION ELIGIBILITY

Pre-permit construction approval is available for new minor sources that do not use emissions netting to stay below major source levels. The proposed project meets all of the pre-permit construction eligibility requirements. The emission calculations and data source reference information are provided in this application.

Andgar is requesting from IDEQ the ability to commence construction of the source before receiving the required permit to construct. The owner understands that proceeding with construction prior to receiving the required permit to construct is at their own risk. This request is presented in the cover letter for this application.

The pre-permit construction process requires a meeting with DEQ representatives before submitting the pre-permit construction permit. Kleinfelder representatives met with Kevin Schilling, Bill Rogers, and Harbi Elshafei of IDEQ on April 9, 2008 to discuss the project and pre-permit application.

An informational meeting has been scheduled at the Jerome City Library on June 4, 2008. The meeting announcement was published in The Times-News which is a newspaper with general circulation in Jerome, Idaho. A copy of the notices published in The Times-News is presented in Appendix E.



3 APPLICABLE REQUIREMENTS

3.1. Major or Minor Facility Designation

The proposed project is considered a minor facility based on it's potential to emit. Please refer to the detailed emission calculations in Appendix D.

Designated: ___Yes __✓_ No Potential To Emit: 98.0 tons/yr

Pollutant which defines Potential to Emit: Carbon Monoxide

3.2. Federal Requirements

No federal regulations other than NSPS SubPart JJJJ (40 CFR 60) are applicable to the proposed project.

The engines will be manufactured after January 1, 2008 and have a capacity greater than 500 hp but less than 1,350 hp and construction will commence after June 12, 2006. Therefore, in accordance with 40 CFR 60.2430, 40 CFR 60, Subpart JJJJ is applicable to this project.

The following NSPS emission standards are applicable to the proposed generators

Table 3-1 Summary of 40 CFR 60, Subpart JJJJ Table 1.

		Manufacture	Emission standards ^a						
Engine Type and	Maximum	Manufacturer	g	g/HP-h	r	ppmvd at 15% O ₂			
Fuel	engine power	Date	NO _x	CO	VOC _p	NOx	CO	VOCb	
Digester Gas (except lean burn 500≤HP<1,350)	HP≥500	7/1/2007	3.0	5.0	1.0	220	610	80	
Digester Gas Lean Burn	500≤HP<1,350	1/1/2008	3.0	5.0	1.0	220	610	80	

^a Owners and operators of stationary non-certified SI engines may choose to comply with the emission standards in units of either g/HP-hr or ppmvd at 15% O₂.

The requirements of 40 CFR 60.4233(f) are applicable to this project. A maintenance plan and records of conducted maintenance will be prepared and available at the site. An initial performance test will be conducted and subsequent performance testing conducted every 8,760 hours or 3-years, whichever comes first. Performance testing will be completed in accordance with the procedures in 40 CFR 60, Subpart JJJJ, Table 2.

40CFR 60.4243(g) does not apply to this application. The engines do not require three-way catalysts /non-selective catalytic reduction to meet the emission standards because

^b For the purposes of this subpart, when calculating emissions of volatile organic compounds (VOC), emission of formaldehyde should not be included.



they are lean burn engines and not rich burning engines. EPA's interpretation of the applicability of this requirement for this type of engines is included in Appendix F.

Notifications will be made in accordance with the NSPS general provisions and Section 60.4245 of 40 CFR 60, Subpart JJJJ.

3.3. Rules for the Control of Air Pollution in Idaho (IDAPA 58.01.01)

IDAPA 58.01.01.123 Certification of Documents

Based on information and belief formed after reasonable inquiry, all statements and information contained in the application are true, accurate, and complete.

IDAPA 58.01.01.128 Confidential Information

The information submitted in the application is subject to public disclosure unless submitted under a secret trade claim.

IDAPA 58.01.01.130 Startup Shutdown, Scheduled Maintenance, Safety Measures, upset and Breakdown

If an excess emission event occurs during startup shutdown, scheduled maintenance, safety measures, upset or breakdown, DF-AP #3 will comply with IDAPA 58.01.01.130 through IDAPA 58.01.01.136.

IDAPA 58.01.01.156 Total Compliance

DF-AP #3 understands that when more than one section of rules applies then all such rules must be met to be considered in compliance.

IDAPA 58.01.01.201 Permit to Construct Required

DF-AP #3 will obtain a permit to construct from the Department which satisfies the requirements of Sections 200 through 208. The proposed project does not meet the permit to construct exemption criteria contained in Sections 220 through 223 of the Rules.

IDAPA 58.01.01.203 Permit Requirements for New and Modified Stationary Sources This permit application demonstrates that the project will comply with all applicable emissions standards, ambient air quality standards, and toxic increments. See the modeling protocol report attached in Appendix B.

IDAPA 58.01.01.210 Demonstration of Preconstruction Compliance with Toxic Standards

This permit application demonstrates preconstruction compliance with the Toxic Standards. See the ambient impacts assessment in Section 5.

IDAPA 58.01.01.223 Exemption Criteria, Recordkeeping, and Reporting for Toxic Air Pollutant Emissions

The proposed project does not meet the exemption criteria specified in sections 01 through 04 of Section 223.



<u>IDAPA 58.01.01.300 Procedures and Requirements of Tier I operating Permits</u>

The facility is not considered a major source and not subject to these requirements.

IDAPA 58.01.01.577 Ambient Air Quality Standards for Specific Air Pollutants
The proposed project meets the ambient air quality standards specified in Section 577.
See the ambient impacts assessment in Section 5.

<u>IDAPA 58.01.01.578 Designation of Attainment, Unclassifiable, and Nonattainment</u> Areas

The proposed project is located in Lincoln County which is currently classified as unclassifiable or attainment for criteria pollutants. DF-AP #3 acknowledges that DEQ annually reviews areas for classification.

IDAPA 58.01.01.585 Toxic Air Pollutants Non-Carcinogenic Increments

The proposed project will result in emissions of non-carcinogenic toxic air pollutants including acrolein, isomers of xylene, selenium, styrene, toluene, and trichloroethylene. These emissions will not exceed their respective screening emission levels with the exception of trichloroethylene. Modeling results indicate emissions for trichloroethylene is below its AAC. See the ambient impacts assessment in Section 5.

IDAPA 58.01.01.586 Toxic Air Pollutants Carcinogenic Increments

The proposed project will result in potential emissions of carcinogenic toxic air pollutants including acetaldehyde, benzene, dichloromethane, formaldehyde, trichloroethylene, nickel and vinyl chloride. The emissions of acetaldehyde does not exceed its screening emission level, however emissions for benzene, dichloromethane, formaldehyde, nickel, trichloroethylene, and vinyl chloride have potential to exceed each of their respective screening emission levels. Modeling results indicate all emissions for carcinogenic toxic air pollutants are below their respective AACCs. See the ambient impacts assessment in Section 5.

IDAPA 58.01.01.590 New Source Performance Standards

DF-AP #3 acknowledges that the proposed project must comply with the NSPS set forth in 40 CFR Part 60. Please see Section 3.2 of this application.

<u>IDAPA 58.01.01.591 National Emission Standards for Hazardous Air Pollutants</u> The proposed project complies with 40 CFR Part 61 and 40 CFR Part 63.

IDAPA 58.01.01.625 Visible Emissions

DF-AP #3 will not discharge any air pollutant which is greater than 20% opacity from the stacks for more than 3 minutes in a 60 minute period. DF-AP #3 will comply with specified test methods and procedures.

IDAPA 58.01.01.650 & 651 Rules for the Control of Fugitive Emissions & General Rules DF-AP #3 will take all reasonable precautions to prevent particulate matter from becoming airborne.



IDAPA 58.01.01.675 & 676 Fuel Burning Equipment – Particulate Matter & Standards for New Sources

The project will not discharge particulate above the applicable grain loading standard.

<u>IDAPA 58.01.01.700--702 Particulate Matter – Process Weight Limitations</u>
The emitting source is not considered process equipment and therefore the regulations do not apply to this source.

IDAPA 58.01.01.760 Rules for the Control of Ammonia from Dairy Farms

The proposed project is located on property leased from the Double A Dairy. The impact analysis for the emissions from the proposed generators demonstrates compliance with applicable standards at the boundary of the leased property. The dairy is owned and operated separately from the generators. Therefore these rules do not apply to this source.

<u>IDAPA 58.01.01.775 Rules for the Control of Odors</u>
All reasonable precautions will be taken to control odors.



4 POTENTIAL EMISSION ESTIMATES

4.1. Equipment and Source Description

Six Guascor 560 electrical generators are proposed to be installed adjacent to each other. The six generators are described in Table 4-1. There are no emission controls proposed for the generators.

Table 4-1
Equipment Description

Equipment Description					
Equipment / Source Description	Emission Controls				
Anaerobic Digester & Electric Generators Anaerobic Digester Capacity: 11,000,000 gallons Throughput: 495,000 gallons per day Biogas Production: 1,754,000 c.f. per day	Internal Combustion Engines (Generator Engines No. 1- 6)				
Generator Engine No. 1 Manufacturer: Guascor Model: SFGLD 560 Rated Power: 1057 horsepower Ignition Type: Spark Generator Engine No. 2 Manufacturer: Guascor Model: SFGLD 560 Rated Power: 1057 horsepower Ignition Type: Spark Generator Engine No. 3 Manufacturer: Guascor Model: SFGLD 560 Rated Power: 1057 horsepower Ignition Type: Spark Generator Engine No. 4 Manufacturer: Guascor Model: SFGLD 560	None				
Rated Power: 1057 horsepower Ignition Type: Spark	· ·				



Generator Engine No. 5

Manufacturer: Guascor Model: SFGLD 560 Rated Power: 1057 horsepower Ignition Type: Spark

None

Generator Engine No. 6

Manufacturer: Guascor Model: SFGLD 560 Rated Power: 1057 horsepower Ignition Type: Spark

4.2. Source Parameters

Each of the generators will have a 12-inch diameter stack extending 28 feet above the ground surface. The vendor estimated, based on the design parameters and modeling the operation of the units, that the typical stack temperatures and velocity will be 630° K and 30.18 meters/second, respectively.

4.3. Emission Factors

The emission factors used to estimate emissions from the generators were obtained from multiple sources including AP-42, EPA's WebFire database and vendor information. The specific vendor information was determined most reliable, since it represents the specific operating conditions and equipment proposed for the project.

AP-42 Section 3.1 has published emission factor data for POTW digester gas-fired stationary gas turbines. In addition, AP-42 Section 3.2 has published emission factors for natural gas fired reciprocating engines. EPA's WebFire database provide limited data from internal combustion engines fueled from POTW digester gas. The WebFire data was collected in the early 1990s and is rated U (unrated)¹ by EPA. It does not provide supporting details about the source and operating conditions.

With the exception of particulate, vendor information was used to estimate emissions for all of the primary pollutants. The PM $_{10}$ and PM $_{2.5}$ emission factors were selected from from AP-42 Section 3.2, Table 3.2 – Uncontrolled Emission Factors for 4-stroke Lean – Burn Engines. The table presents D-Rated PM-10 (filterable) and PM Condensible emission factors for natural gas lean burn reciprocating engines. The PM-10 emissions represent the sum of the PM-10 (filterable) and the PM Condensable fractions, since the condensable fraction is likely less than 10 microns.

TAP emission data from generators using digester gas fuel is likely more representative than data from generators using natural gas fuel. AP-42 Section 3.2, Table 3.1-7

Emission factor is developed from source tests which have not been thoroughly evaluated, research papers, modeling data, or other sources that may lack supporting documentation. The data are not necessarily "poor," but there is not enough information to rate the factors according to the rating protocol. "U" ratings are commonly found in L&E documents and FIRE rather than in AP-42.



Emission Factors for Hazardous Air Pollutants from Digester Gas-Fired Stationary Gas Turbines presents D-Rated uncontrolled emission factors acetaldehyde, formaldehyde, nickel and selenium. Other HAPs are presented in the data, but reported as nondetectable. The remaining emission factors were extracted from the EPA WebFire database. This data was identified as the least reliable of the available data. It is unrated by EPA and provides no supporting information to evaluate its relevance to the proposed project.

4.4. Potential to Emit / Emissions Estimates

The potential to emit for the proposed project is shown in Table 4-2. Please see Appendix D for detailed emission calculations.

The generators will emit acrolein, isomers of xylene, styrene, toluene, selenium and trichloroethylene which are non-carcinogenic toxic air pollutants (TAPs) listed in IDAPA 58.01.01.585. The potential emission estimates for these compounds do not exceed screening emission levels (EL) with the exception of their respective TAP emit acetaldehvde. generators will also trichloroethylene. The dichloromethane, formaldehyde, nickel, trichloroethylene and vinyl chloride which are carcinogenic TAPs listed in IDAPA 58.01.01.586. The potential emission estimates for acetaldehyde does not exceed its TAP EL. However, modeling was conducted for benzene, dichloromethane, formaldehyde, nickel, trichloroethylene, and vinyl chloride because potential emission estimates exceed their respective TAP ELs. Modeling demonstrates compliance with the Acceptable Ambient Concentrations (AACs).

Table 4-2
Potential Emission Rates for Genset Generators

Pollutant	PTE	PTE
	(lbs/hr)	(tons/yr)
PM ₁₀	0.41	1.80
SO ₂	3.09	13.5
NO _x	13.98	61.2
CO	22.37	98.0
VOC	13.98	61.2
Acetaldehyde	2.2E-03	9.6E-03
Acrolein	1.1E-03	4.7E-03
Benzene	2.8E-02	1.2E-01
Dichloromethane	4.2E-03	1.8E-02
Formaldehyde	7.8E-03	3.4E-02
Isomers of Xylene	5.6E-03	2.5E-02
Nickel	8.3E-05	3.6E-04



Pollutant	PTE	PTE
	(lbs/hr)	(tons/yr)
Selenium	4.5E-04	2.0E-03
Styrene	2.2E-03	9.5E-03
Toluene	1.1E-02	4.7E-02
Trichloroethylene	8.3E-04	3.6E-03
Vinyl Chloride	2.3E-03	1.0E-02

4.5. Emission Limits

The concentration of the Hydrogen Sulfide (H_2S) entering the generators from anaerobic digester shall not exceed 250 ppm. A H_2S scrubbing system will be installed between the anaerobic digester and the generators to reduce the amount of H_2S entering the generators and thus reducing the emissions of SO_2 from the generators. DF-AP #3 proposes to perform the following to monitor the quantity of H_2S leaving the H_2S scrubbing system:

- Within 120 days of startup, DF-AP #3 will install, calibrate, maintain, operate, and record an H₂S gas monitor that will be placed down stream of the H₂S scrubbing system and upstream of the electric generators, and the biogas flare to measure the H₂S concentrations in the biogas leaving the scrubbing system. The monitor will be installed in accordance with the O&M manual and the manufacturer's specifications.
- Calibration of the H₂S monitor will be performed and recorded semiannually or per manufacturer's recommendations.
- The results of the H2S concentrations from the H2S monitor will be recorded once per week. The H2S monitoring will be re-evaluated after reaching maximum operating capacity and review of H2S concentration data. The frequency may be modified with IDEQ approval.

The H_2S produced by the digester is based on the biogas production of 1,754,000 cubic feet of biogas per day. This is the maximum biogas that the digester will produce in one day based on the production of other digesters in operation.

DF-AP #3 propose to perform the following to monitor the volume of biogas produced by the anaerobic digester per day:



- Within 120 days of startup, DF-AP #3 will install, calibrate, maintain, operate, and record a gas flow meter that will be placed down stream of digester and upstream of the electric generators, and the biogas flare to measure the amount of biogas produced by the anaerobic digester. The monitor will be installed in accordance with the O&M manual and the manufacturer's specifications.
- Calibration of the gas flow meter will be performed and recorded semiannually or per manufacturer's recommendations.
- The results of the gas flow meter will be recorded once per day. The biogas volume monitoring will be re-evaluated after reaching maximum operating capacity and review of biogas volume data.



5 AMBIENT IMPACT ASSESSMENTS

Air quality modeling was conducted consistent with the Idaho Department of Environmental Quality (IDEQ) Dispersion Modeling Guidelines (Guidelines), revised December 31, 2002, and the Ambient Air Quality Modeling Protocol for this project submitted to IDEQ and approved April 19, 2008. The Screen3 output files are attached in Appendix D.

Tables 5-1 and 5-2 below show the modeled results of the ambient air impacts from the proposed source emissions at the leased property boundary line. The modeled impacts from criteria pollutants are compared to National Ambient Air Quality Standards (NAAQS). The modeled impacts from TAPs are compared to State of Idaho AACs and AACCs.

Table 5-1

Modeling Results for Criteria Pollutants (ug/m³)

	modeling restate for enterior (ag.m.)								
	SO₂		PM ₁₀		С	0	NO2	Pb	
	3-Hr	24-Hr	Annual	24-Hr	Annual	1-Hr	8-Hr	Annual	Qtrly
Modeled	89.25	39.67	7.93	5.30	1.06	719.04	503.33	26.96	n/a
Background	34	26	8	73	26	3600	2300	17	n/a
Total	123.25	65.67	15.93	78.30	27.06	4319.04	2803.33	43.96	n/a
NAAQS	1300	365	80	150	50	40,000	10,000	100	1.5

Table 5-2
Modeling Results for TAPs (ug/m³)

Pollutant	Modeled Ambient Conc	AAC/AACC	
Acetaldehyde	Acetaldehyde Below TAP EL		
Acrolein	Below TAP EL	n/a	
Benzene	0.11	0.12	
Dichloromethane	0.017	0.24	
Formaldehyde	0.031	0.077	
Isomers of Xylene	Below TAP EL	n/a	
Nickel	0.0003	0.0042	
Selenium	Below TAP EL	n/a	
Styrene	Below TAP EL	n/a	
Toluene	Below TAP EL	n/a	
Trichloroethylene	24 hour 0.011 Annual 0.003	24 hour 13,450 Annual 0.77	
Vinyl Chloride	0.009	0.14	



Tables 5-3 and 5-4 below show the modeled results of the ambient air impacts approximately ½ mile west of the proposed source emissions. The elevated terrain was evaluated using the complex terrain option in Screen3. Tables 5-3 and 5-4 show the modeled results at the plume height of 36.6 meters. The modeled impacts from criteria pollutants are compared to National Ambient Air Quality Standards (NAAQS). The modeled impacts from TAPs are compared to State of Idaho AACs and AACCs.

Based on the analysis performed, the proposed stationary source will not cause or significantly contribute to a violation of any ambient air quality standard and demonstrates pre-construction compliance with IDAPA 58.01.01, Section 161 with regards to TAP emissions.

Table 5-3
Modeling Results for Criteria Pollutants (ug/m³)


	1110001119 110001110 101 011101111 101101111								
	SO ₂			PM ₁₀		CO		NO2	Pb
	3-Hr	24-Hr	Annual	24-Hr	Annual	1-Hr	8-Hr	Annual	Qtrly
Modeled	25.63	11.39	2.28	1.52	6.30	206.47	144.53	7.74	n/a
Background	34	26	8	73	26	3600	2300	17	n/a
Total	59.63	37.39	10.28	74.52	26.30	3806.47	2444.53	24.74	n/a
NAAQS	1,300	365	80	150	50	40,000	10,000	100	1.5


Table 5-4
Modeling Results for TAPs (ug/m³)


Pollutant	Modeled Ambient Conc	AAC/AACC
Acetaldehyde	Below TAP EL	n/a
Acrolein	Below TAP EL	n/a
Benzene	0.03	0.12
Dichloromethane	0.005	0.24
Formaldehyde	0.009	0.077
Isomers of Xylene	Below TAP EL	n/a
Nickel	0.0001	0.0042
Selenium	Below TAP EL	n/a
Styrene	Below TAP EL	n/a
Toluene	Below TAP EL	n/a
Trichloroethylene	24 hour 0.003	24 hour 13,450
	Annual 0.001	Annual 0.77
Vinyl Chloride	0.003	0.14




FIGURES











APPENDIX A

Permit to Construct Application Forms

May 22, 2008

Department of Environmental Quality Air Quality Division Stationary Source Program 1410 North Hilton Boise, ID 83706-1255

ATTN: Air Quality Division

RE: 15-Day Pre Permit Construction Approval Application

Dear DEQ,

We are proposing to construct an anaerobic digester on Double A Dairy that will collect the biogas from the cow manure and transform it into renewable energy through the use of six reciprocating engines and generators. A letter from Kleinfelder is included in the application demonstrating that they have performed the screening level modeling and found that the proposed emissions will not cause or significantly contribute to a violation of any air quality standards. A copy of the approved modeling protocol and a copy of the public notice meeting are also attached. Please review the attached application for the 15-Day pre-permit construction approval and let us know if you have any questions.

Kyle Juergens with Andgar Corporation is our representative for this application. Please send all correspondence to him. (360-366-9900 or kylej@andgar.com)

Based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Sincerely,

Marlin Statema DF-AP #3, LLC



DEQ AIR QUALITY PROGRAM 1410 N. Hilton, Boise, ID 83706 For assistance, call the Air Permit Hotline – 1-877-5PERMIT

PERMIT TO CONSTRUCT APPLICATION

Revision 3 04/03/07

Please see instructions on page 2 before filling out the form.

C	OMPANY	NAME, FACILITY NAME, AND FACILITY ID NUMBE	R			
1. Company	y Name	DF-AP #3, LLC				
2. Facility I	Name	Double A Dairy Digester 3. Facility ID No. 1				
4. Brief Pro	oject Descrip	otion - Dairy Anaerobic Digester which captures biogas to produce through gensets.	electricity			
		PERMIT APPLICATION TYPE				
		New Source at Existing Facility Unpermitted Existing Sc	urce			
—		Source: Permit No.: Date Issued:				
		orcement Action: Case No.:				
6. Mino	or PTC	☐ Major PTC FORMS INCLUDED				
			DEQ			
Included	N/A	Forms	Verify			
		Form GI – Facility Information				
	\boxtimes	Form EU0 – Emissions Units General				
\boxtimes		Form EU1 - Industrial Engine Information Please Specify number of forms attached:				
	\boxtimes	Form EU2 - Nonmetallic Mineral Processing Plants Please Specify number of forms attached:				
	\boxtimes	Form EU3 - Spray Paint Booth Information Please Specify number of forms attached:				
		Form EU4 - Cooling Tower Information Please Specify number of forms attached:				
. 🔲	\boxtimes	Form EU5 – Boiler Information Please Specify number of forms attached:				
		Form HMAP – Hot Mix Asphalt Plant Please Specify number of forms attached:				
		Form CBP - Concrete Batch Plant Please Specify number of forms attached:				
		Form SCE - Scrubbers Control Equipment				
\boxtimes		Forms EI-CP1 - EI-CP4 - Emissions Inventory- criteria pollutants (Excel workbook, all 4 worksheets)				
		PP – Plot Plan				
\boxtimes	. 🔲	Forms MI1 – MI4 – Modeling (Excel workbook, all 4 worksheets)				
		Form FRA – Federal Regulation Applicability				

DEQ USE ONLY Date Received
Project Number
Payment / Fees Included? Yes No No
Check Number



PERMIT TO CONSTRUCT APPLICATION

Revision 3 03/26/07

Please see instructions on page 2 before filling out the form.

All information is required. If information is missing, the application will not be processed.

1444.4	IDENTIFICATION
1. Company Name	DF-AP #3, LLC
2. Facility Name (If different than #1)	Double A Dairy Digester
3. Facility I.D. No.	1
4. Brief Project Description:	Dairy anaerobic digester which captures biogas to produce electricity through
	FACILITY INFORMATION
5. Owned/operated by: {√ if applicable}	Federal government County government State government City government
6. Primary Facility Permit Contact Person/Title	Marlin Statema - Manager
7. Telephone Number and Email Address	360-392-8938 or mstatema@comcast.net
8. Alternate Facility Contact Person/Title	Gary VanLoo
9. Telephone Number and Email Address	360-366-9900 garyv@andgar.com
10. Address to which permit should be sent	PO Box 2708
11. City/State/Zip	Ferndale, WA 98248
12. Equipment Location Address (if different than #10)	305 County Line Rd.
13. City/State/Zip	Jerome, ID 83338
14. Is the Equipment Portable?	Yes No
15. SIC Code(s) and NAISC Code	Primary SIC: 1629 Secondary SIC (if any): NAICS: 237130
16. Brief Business Description and Principal Product	Anaerobically digest cow manure and capture methane to power engine and produce electricity.
17. Identify any adjacent or contiguous facility that this company owns and/or operates	
	PERMIT APPLICATION TYPE
18. Specify Reason for Application	 New Facility ☐ New Source at Existing Facility ☐ Unpermitted Existing Source ☐ Modify Existing Source: Permit No.: Date Issued: ☐ Permit Revision ☐ Required by Enforcement Action: Case No.:
	CERTIFICATION
IN ACCORDANCE WITH IDAPA 58.01.01.123 (R AFTER REASONABLE INQUIRY,	ULES FOR THE CONTROL OF AIR POLLUTION IN ÍDAHO), Í CERTIFY BASED ON INFORMATION AND BELIEF FORMED THE STATEMENTS AND INFORMATION IN THE DOCUMENT ARE TRUE, ACCURATE, AND COMPLETE,
19. Responsible Official's Name/Title	Marlin Statema - Manager
20. RESPONSIBLE OFFICIAL SIGNATU	RE M 1 1 Date: 5-22-08
21, Check here to indicate you would	like to review a draft permit prior to final issuance.

Emissions Units - Industrial Engine Information Form EU1



DEQ AIR QUALITY PROGRAM 1410 N. Hilton, Boise, ID 83706 For assistance, call the Air Permit Hotline – 1-877-5PERMIT

PERMIT TO CONSTRUCT APPLICATION

Revision 3 03/27/07

Please see instructions on page 2 before filling out the form.

IDENTIFICATION						
Company Name:		Facility Name:		Facility	ID No:	
DF-AP #3, LLC		Double A Dairy Digester		1		
Brief Project Description:		Dairy Anaerobic Digester that collects biogas & makes electricity				
EXEMPTION						
Please refer to IDAPA 58.01.01.222.01.c and d for a list of internal combustion engines that are exempt from the Permit to Construct requirements.						
ENGINE (EMISSION UNIT) DESCRIPTION AND SPECIFICATIONS						
1. Type of Unit: New Unit Unpermitted Existing Unit Date Issued:						
2. Use of Engine: Normal Operation Emergency Back-up Other: Renewable Energy						
3. Engine ID Number: 4. R			Rated Power:			
1 1						
5. Construction Date: 6.		i. Manufacturer: 7.		7. Model:		
5/1/08		Guascor		SFGLD 560		
8. Date of Modification (if applicable): 9.		Serial Number (if available):		10. Control Device (if any):		
FUEL DESCRIPTION AND SPECIFICATIONS						
11.	☐ Diesel Fuel (#)		☐ Gasoline Fuel	☐ Natural Gas		
Fuel Type	(gal/hr)		(gal/hr)	(cf/hr)	(unit:cf/hr)	
12. Full Load Consumption Rate					12,532	
13. Actual Consumption Rate					12,185	
14. Sulfur Content wt%			N/A	N/A		
OPERATING LIMITS & SCHEDULE						
15. Imposed Operating Limits (hours/year, or gallons fuel/year, etc.):						
16. Operating Schedule (hours/day, months/year, etc.):						
24 hours a day 365 days a year						